TACENS

VENTUS II ICE 12

12 cm **9 dB**

Revolutionary 15 air-guiding Fan Blades for unprecedented airflow performance with ultra-low noise level.

Exclusive FLUXUS PRO II bearing based in Fluid Dynamic Bearing Technology for more than 200.000 hrs lifespan and ultra-silent operation.

•Special Voltage reduction cable included for Ultra-performance or Ultra-quiet operation.
•Professional Anti-vibration screws, 3-4pin adaptor and black sleeved cables included.
•Ultra-silent: 9dB-15dB and Ultra-Airflow: 32.5-78 CFM
• Four White leds for COOL lighting effect.

ICE Model

DESIGNED IN EUROPE

Standard Connection	
Rated Voltaje:	12V
Starting Voltaje:	≤ 6V
Power Consumption:	2.16W
Rated Current:	0.18A
Speed:	1200 RPM±10%
Air Flow:	78 CFM
Air Pressure:	0.686 mm -H_2O
Noise:	15dBA
MTBF:	200.000 hours

Connect with Voltage reduction cable	
Rated Voltaje:	(To FAN)7V
Starting Voltaje:	≤ 6V
Power Consumption:	1.2W
Rated Current:	0.10A
Speed:	700 RPM±10%
Air Flow:	32.5 CFM
Air Pressure:	0.305 mm -H_2O
Noise:	9dBA
MTBF:	200.000 hours

Features & Especifications